

ONWA[®]

COLOR ECHO SOUNDER DUAL-frequency, 5.6-inch display

Model **KF-667**

- Dual-frequency: 50 and 200KHz
- 5.6-inch TFT LCD display with 8-color or multi-level amber presentation
- Auto Mode for hands-off operation
- Variety of display modes: A-scope, bottom-lock expansion, marker zoom and unique bottom zoom displays
- Temperature sensor option



SPECIFICATIONS

1. GENERAL

- (1) Display 5.6-inch TFT LCD
(2) Echo Color 8 colors (including background color) according to echo intensity. Monochrome display is also available. The background color is selectable from blue, light blue, white and black.
- (3) Basic Range Meters: 5/10/20/40/80/150/200/300
Feet: 15/30/60/120/200/400/600/1000
Fathoms: 3/5/10/20/40/80/100/150
Passi/Braza: 3/5/10/30/50/100/150/200
The basic ranges can be changed on the system menu.
- (4) Range Shift Up to 300 meters (1000 feet, 150 fathoms, 200 passi/braza)
- (5) Zoom Range Times 2, 3, 4 and 5 ranges
- (6) Bottom Lock Expansion Range 5/10 meters, 10/20 feet, 2/5 fathoms, 2/5 passi/braza
- (7) Auto Mode Automatic adjustment of range and gain
- (8) Display Mode High Frequency (200K), Low Frequency (50K), Dual (200K and 50K 1/2 display on each), Zoom (200K and 50K zoom) and A-scope Display
- (9) Zoom Display Marker Zoom, Bottom Zoom and Bottom-lock Expansion
- (10) Display Advance Speed Lines/TX: Freeze, 1/8, 1/4, 1/2, 1/1, 2/1
- (11) TX Frequency Output power 50 and 200kHz (alternately transmitted), 300W
- (12) Pulse-length/TX rate

| | | | | | | | |
|----------------------|-----|-----|-----|-----|-----|-----|-----|
| Display End Depth(m) | 5 | 10 | 20 | 40 | 80 | 150 | 300 |
| Pulse-Length(ms) | 0.2 | 0.2 | 0.2 | 0.4 | 0.8 | 1.5 | 3.0 |
| TX Rate(pulse/min) | 600 | 600 | 600 | 375 | 187 | 100 | 50 |

- (13) Interference Rejecter Rejects unwanted signals by comparing last and present echoes in strength.
- (14) Alarm Fish and Bottom alarms, Temperature alarm (sensor required)
- (15) Input/output data NMEA 0183
Input RMC, VTG
Output SDDBT, SDDPT

2. POWER SUPPLY

- (1) Display Unit 12-24 VDC (-10%, +30%) : 1.0 - 0.6 A

3. ENVIRONMENTAL CONDITION

- (1) Ambient Temperature 0°C to +50°C
- (2) Relative Humidity 85% at 40°C
- (3) Water proofing Display Unit: IPX4
- (4) Vibration $\pm 1\text{mm } \pm 10\%$, 2(5) to 13.2Hz,
Maximum acceleration 7 m/s^2 , 13.2 to 100Hz

4. COATING COLOR

- (1) Display Unit Chassis: 2.5GY5/1.5
Panel: N3.0 Newton No.5

DISPLAY UNIT

